

# ENEOS Premium Hyper 5W30

## Fully-Synthetic long-life motor oil

ENEOS Premium Hyper 5W30 is ultra-modern fully-synthetic motor oil for gasoline & diesel engines in passenger cars & light commercial vehicles equipped with or without catalytic converter, soot filters, turbo charged and direct injection systems. This oil guarantees rapid and stable lubrication, high thermal stability under heavy-duty conditions in a broad temperature range. This low SAPS Oil covers all European, American & Japanese passenger car engines and ensures extended drain, cleaner combustion, enhanced fuel economy, low oil consumption and low emission levels

### ● SPECIAL FEATURES

#### 1. Fully-Synthetic Motor Oil with Deposit control Formula

Low "SAPS" new generation Oil offering extremely high protection over prolonged drain intervals. Especially recommended for Euro-IV cars from Mercedes Benz, BMW and Japanese cars with soot filters to prevent filter blocking. Reinforces the action of Diesel Particulate Filter and prolongs its lifespan, by avoiding its early blinding

#### 2. Longer Drain Intervals

Ensures exceptional engine durability and allows the extra long oil drain intervals, thanks to its exceptional oxidation resistance.

#### 3. Superior Wear Resistance and Excellent Cleanliness

Maintain strong oil film at high temperatures, speeds, and loads. Its antiwear protection is particularly effective in the drive trains of overhead cam systems. This oil also has superb thermal and oxidation stability, so it maintains excellent engine cleanliness by suppressing sludge formation, which can cause engine seizures & pump clogging

### ● PERFORMANCE LEVELS

- API SN/SM/CF
- ACEA C3 (10) A3/B3/B4 (08)
- VOLKSWAGEN: 505 00/505 01/502 00
- MERCEDES-BENZ: MB 229.51 & 229.31
- BMW LongLife 04
- GM Dexos 2

### ● APPLICABLE VEHICLES

Gasoline and Diesel engines in passenger cars and light duty commercial vehicles, equipped with or without catalytic converters or DPF, soot filters, direct injection systems and turbo charged engines.

Suitable for Volkswagen Group cars (VW, Seat, Audi, Skoda, Porsche) with normal drain intervals. Suitable for BMW, Mercedes Benz, GM and Japanese cars & light commercial vehicles with extended drain intervals.

### ● CONTAINERS

1L, 4L, 20L, 200L and 1000L IBC

### ● TYPICAL PROPERTIES

SAE viscosity grade	5W-30
Density (20°C), g/cm <sup>3</sup>	0.849
Flash point (COC), °C	225
Kinematic viscosity (40°C), mm <sup>2</sup> /s	71.8
(100°C), mm <sup>2</sup> /s	12.0
Viscosity index	164
Pour point, °C	-42.0

Note: The typical properties may be changed without notice. (April 2016)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.